

APPEARANCE

PART NUMBER







DIMENSION [mm]

IMPEDANCE [Ω] $\pm 15\%$ NORMAL POWER P_w [mW]SPL (@ $P_w / 0.5$ m) [dB]OPERATING TEMPERATURE [$^{\circ}$ C]LOWEST RESONANT FREQUENCY f_0 [Hz]

FREQUENCY RANGE (SPL-10dB) [Hz]

Dynamic Speakers – Round/Oval Type with Fabric/Mylar/Titanium Cone



	23CS08FH	\emptyset 23.0 \times 5.4	8	500	82	-20 ... +60	900	600 ... 20000
	2512VM08S	24.5 \times 12.0 \times 4.9	8	1000	81	-20 ... +60	850	400 ... 20000
	26CR08F	\emptyset 26.0 \times 4.4	8	500	83	-20 ... +60	540	450 ... 20000
	26CS08F	\emptyset 26.0 \times 4.4	8	500	81	-20 ... +60	470	250 ... 5500
	26CRF04E-1	\emptyset 26.0 \times 4.3	4	1500	83	-20 ... +60	740	400 ... 20000
	26CR08FE	\emptyset 26.0 \times 4.4	8	500	85	-40 ... +85	670	450 ... 20000
	26CS08G	\emptyset 26.0 \times 4.4	8	500	83	-20 ... +60	520	400 ... 8000
	28CS08FL	\emptyset 28.0 \times 3.9	8	1000	85	-20 ... +60	620	400 ... 6500
	28CS08FN-2	\emptyset 28.0 \times 4.2	8	500	85	-20 ... +60	680	400 ... 7000
	28CS08G	\emptyset 28.0 \times 4.3	8	200	82	-20 ... +60	850	600 ... 5600
	28CS08GQ-1	\emptyset 28.0 \times 5.0	8	200	82	-20 ... +60	850	600 ... 5600
	28CR08FH	\emptyset 28.0 \times 5.5	8	500	80	-40 ... +85	350	200 ... 20000