

シリコン整流スタック・ブリッジ Bridge type

品名	色別	Io (A)	VRM (V)	IFSM (A)	VF (max.) (V)	IR (max.) (μA)	外形図
SIYB10	0.4	0.4	100	30	1.05	10	19
SIYB20			200				
SIYB40			400				
SIYB60			600				
SIWB10	0.6	0.6	100	30	1.05	10	20
SIWB20			200				
SIWB40			400				
SIWB60			600				
SIVB10	0.6	0.6	100	30	1.05	10	21
SIVB20			200				
SIVB40			400				
SIVB60			600				
SIRBA10	1	1	100	30	1.05	10	22
SIRBA20			200				
SIRBA40			400				
SIRBA60			600				
SIRBA80	800						
SIRBA20Z	1	1	200	30	1.05	10	22
SIRBA40Z			400				
S2VB10	2	2	100	40	1.05	10	23
S2VB20			200				
S2VB40			400				
S4VB10	4	4	100	80	1.05	10	24
S4VB20			200				
S4VB40			400				
S4VB60	600						
S5VB10	6	6	100	200	1.05	10	25
S5VB20			200				
S5VB40			400				
S5VB60	600						
SI0VB10	10	10	100	200	1.05	10	26
SI0VB20			200				
SI0VB40			400				
SI0VB60			600				
SI5VB10	15	15	100	200	1.05	10	27
SI5VB20			200				
SI5VB40			400				
SI5VB60			600				
S25VB10	25	25	100	400	1.05	10	28
S25VB20			200				
S25VB40			400				
S25VB60			600				
D4BB10	4.5	4.5	100	200	1.05	10	29
D4BB20			200				
D4BB40			400				
D5FB10	5	5	100	200	1.05	10	30
D5FB20			200				
D5FB40			400				

シリコン整流スタック・センタタップ Center-tapped Diodes

品名	色別	Io (A)	VRM (V)	IFSM (A)	VF (max.) (V)	IR (max.) (μA)	外形図
S3VC10	無	2.5	200	120	1.05	10	31
S3VC10R							
S3VC20	赤	2.5	200	120	1.05	10	31
S3VC20R							
S3VC40	黄	2.5	400	120	1.05	10	31
S3VC40R							

サイダック (2方向2端子サイリスタ) SIDAC Bi-directional diode thyristors

形名	色別	IT (A)	VDRM (V)	ITSM (A)	VBO (V)	IBO (max.) (mA)	VT (max.) (V)	外形図
KIV5	赤	1	45	13	45~60	0.5	1.5	32
KIV6	金				55~65			
KIV10	橙	1	90	13	95~113	0.5	1.5	32
KIV11	青				104~118			
KIV12	緑	1	90	13	110~125	0.5	1.5	32

