

シリコン整流スタック・ブリッジ Bridge type

| 品名 | 色別 | Io (A) | VRM (V) | IFSM (A) | VF (max.) (V) | IR (max.) (μA) | 外形図 |
|----------|-----|--------|---------|----------|---------------|----------------|-----|
| SIYB10 | 0.4 | 0.4 | 100 | 30 | 1.05 | 10 | 19 |
| SIYB20 | | | 200 | | | | |
| SIYB40 | | | 400 | | | | |
| SIYB60 | | | 600 | | | | |
| SIWB10 | 0.6 | 0.6 | 100 | 30 | 1.05 | 10 | 20 |
| SIWB20 | | | 200 | | | | |
| SIWB40 | | | 400 | | | | |
| SIWB60 | | | 600 | | | | |
| SIVB10 | 0.6 | 0.6 | 100 | 30 | 1.05 | 10 | 21 |
| SIVB20 | | | 200 | | | | |
| SIVB40 | | | 400 | | | | |
| SIVB60 | | | 600 | | | | |
| SIRBA10 | 1 | 1 | 100 | 30 | 1.05 | 10 | 22 |
| SIRBA20 | | | 200 | | | | |
| SIRBA40 | | | 400 | | | | |
| SIRBA60 | | | 600 | | | | |
| SIRBA80 | 800 | | | | | | |
| SIRBA20Z | 1 | 1 | 200 | 30 | 1.05 | 10 | 22 |
| SIRBA40Z | | | 400 | | | | |
| S2VB10 | 2 | 2 | 100 | 40 | 1.05 | 10 | 23 |
| S2VB20 | | | 200 | | | | |
| S2VB40 | | | 400 | | | | |
| S4VB10 | 4 | 4 | 100 | 80 | 1.05 | 10 | 24 |
| S4VB20 | | | 200 | | | | |
| S4VB40 | | | 400 | | | | |
| S4VB60 | 600 | | | | | | |
| S5VB10 | 6 | 6 | 100 | 200 | 1.05 | 10 | 25 |
| S5VB20 | | | 200 | | | | |
| S5VB40 | | | 400 | | | | |
| S5VB60 | 600 | | | | | | |
| SI0VB10 | 10 | 10 | 100 | 200 | 1.05 | 10 | 26 |
| SI0VB20 | | | 200 | | | | |
| SI0VB40 | | | 400 | | | | |
| SI0VB60 | | | 600 | | | | |
| SI5VB10 | 15 | 15 | 100 | 200 | 1.05 | 10 | 27 |
| SI5VB20 | | | 200 | | | | |
| SI5VB40 | | | 400 | | | | |
| SI5VB60 | | | 600 | | | | |
| S25VB10 | 25 | 25 | 100 | 400 | 1.05 | 10 | 28 |
| S25VB20 | | | 200 | | | | |
| S25VB40 | | | 400 | | | | |
| S25VB60 | | | 600 | | | | |
| D4BB10 | 4.5 | 4.5 | 100 | 200 | 1.05 | 10 | 29 |
| D4BB20 | | | 200 | | | | |
| D4BB40 | | | 400 | | | | |
| D5FB10 | 5 | 5 | 100 | 200 | 1.05 | 10 | 30 |
| D5FB20 | | | 200 | | | | |
| D5FB40 | | | 400 | | | | |

シリコン整流スタック・センタタップ Center-tapped Diodes

| 品名 | 色別 | Io (A) | VRM (V) | IFSM (A) | VF (max.) (V) | IR (max.) (μA) | 外形図 |
|---------|----|--------|---------|----------|---------------|----------------|-----|
| S3VC10 | 無 | 2.5 | 100 | 120 | 1.05 | 10 | 31 |
| S3VC10R | | | 200 | | | | |
| S3VC20 | 赤 | 2.5 | 200 | 120 | 1.05 | 10 | 31 |
| S3VC20R | | | 400 | | | | |
| S3VC40 | 黄 | 2.5 | 400 | 120 | 1.05 | 10 | 31 |
| S3VC40R | | | 800 | | | | |

サイダック (2方向2端子サイリスタ) SIDAC Bi-directional diode thyristors

| 形名 | 色別 | IT (A) | VDRM (V) | ITSM (A) | VBO (V) | IBO (max.) (mA) | VT (max.) (V) | 外形図 |
|-------|----|--------|----------|----------|---------|-----------------|---------------|-----|
| KIV5 | 赤 | 1 | 45 | 13 | 45~60 | 0.5 | 1.5 | 32 |
| KIV6 | 金 | | | | 55~65 | | | |
| KIV10 | 橙 | 1 | 90 | 13 | 95~113 | 0.5 | 1.5 | 32 |
| KIV11 | 青 | | | | 104~118 | | | |
| KIV12 | 緑 | 1 | 90 | 13 | 110~125 | 0.5 | 1.5 | 32 |