

# LED ドットマトリックス

# LED Dot Matrix Displays

Ta=25°C

ドット構成 Dot Configuration	機種名 Type No.		波長 Peak Wave-length	絶対最大定格 Absolute Maximum Ratings					推奨動作電流 IFP/dot Recommend.	電氣的・光学的特性 Electro-Optical Characteristics					
				IF/dot	IFP/dot	VR/dot	P <sub>D</sub>	Topr		V <sub>F</sub> Typ.	I <sub>F</sub>	Luminous Intensity		I <sub>R</sub> Max. (V <sub>R</sub> =3V) μA	
	mA	mA	V	W	°C	mA	V	mA	cd/m <sup>2</sup>			Typ.	I <sub>F</sub>		
8 x 8	Com.-Anode	Com.-Cathode	SLA-3764	567 (Y.G)	(15)	50	3	0.8	-20~50	20~30 (D1/8)	2.0	10	460	10	10
		Com.-Cathode	SLA-6764	610 (O)	(15)	50	3	0.8	-20~50	20~30 (D1/8)	2.0	10	300	10	10
		Com.-Cathode	SLA-9764	630 (U.R)	(15)	50	3	0.8	-20~50	20~30 (D1/8)	1.9	10	300	10	10

## 外観図

## Package Dimensions

SLA-□764

